

Marcatrice a
freddo per metalli

S29

Metal
Cold Marker

Sostituisce la tecnica di marcatura manuale con
martello e punzone.

Ideale per marcatura al di fuori delle officine,
perché completamente autonoma
da alimentazioni esterne.



*It replaces manual marking with a hammer and punch.
Ideal to mark when not at the workshop
as it does not require any external supply source.*

- ✓ Marcatura di identificazione di semilavorati quali lastre, billette, lingotti, tondi (sulla sezione);
- ✓ Marcatura di numeri di serie su parti di impianto, strutture metalliche, telai di rimorchi, carri ferroviari, impianti di sollevamento, macchine utensili.

Potenza : Marcatura a freddo, su superfici piane, di acciaio o metalli in genere di resistenza caratteristica massima = 1.200 N/mm²

Caratteri : Altezza 6 - 8 - 10 - 12 mm
Capacità testa 8 caratteri

Peso attrezzo : 3,1 kg

Lunghezza a canna chiusa : 352 mm

Ø esterno pistone : 16 mm

Forza di appoggio (sicurezza) : 15 da N (kg)

Classificazione di sicurezza : Classe A,
Categoria A* - Omologazione C.I.P. n° 001044
Tiro indiretto. Protezione contro il tiro libero.

Dotazione : Prodotti per pulizia ordinaria (panno, scovoli, spazzola, spray decapante)
Effettuare la pulizia (spazzolatura) del meccanismo canna-pistone ogni 500 colpi.
Non lubrificare l'interno della canna.

- ✓ Id marking of semi-finished products such as sheets, billets, bullions, round sections (on their section);
- ✓ Marking of serial numbers on equipment sections, metal structures, trailer frames, railway wagons, lifting equipment, machine tools.

Power : Cold marking on flat or steel surfaces or on metals in general providing a maximum nominal strength = 1.200 N/mm²

Types : 6 - 8 - 10 - 12 mm in height
Head capacity of 8 types

Tool Weight : 3,1 kg

Length with closed cane : 352 mm

Piston Outer Ø : 16 mm

Bearing force (safety) : 15 da N (kg)

Safety Class : Class A, Category A* -
C.I.P. Homologation no. 001044 - Indirect
Stroke. Protection against free strokes.

Standard Supply : Products for normal cleaning (cloth, swabs, brush, stripping spray).
Clean (brushing) the cane-piston mechanism every 500 strikes.

Never lubricate the internal part of the cane.

SOMAUT
marking solutions

SOMAUT S.r.l.

Via Calatafimi 4

20019 **SETTIMO MILANESE** (MI) - ITALY

Tel. 02.453.294.96 - Fax 02.936.505.06

Internet: www.somaut.com - E-Mail: info@somaut.com